


LARGE DIAMETER CIRCULAR KNITTING MACHINE ZENIT HS






LARGE DIAMETER ZENIT HS







LARGE DIAMETER ZENIT HS


Single jersey four cam track machine.

LARGE DIAMETER ZENIT HS

ZENIT HS

- Single jersey machine with 3 feeders per diameter inch capable to knit up to 4 track structures, with/without lycra.
- Excellent to knit two or three yarn plaited fabrics.
- Double guidance sinker cams in combination with well designed sinkers with tail ensures uniform loops all over the fabric and less wear and tear of sinkers.
- Machine is equipped with enconomical and common needles easily available all over the word.
- Yarn carrier in front of the raised needles for a perfect plating at high speed.
- Individual cam shells made by special aluminum alloy (ergal) having a great heat dissipation property.
- Automatic positioning of the fabric take down for quick removal of fabric roll.
- Possibility to convert the machine for the production of three thread fleece.
- Available with tubular as well as Open width frame(standard and industrial)equipped with motorized slitting and opening system by oblique bars.
- Open version can easily be converted into tubular from by a simple operation.
- Very compact open frame for an easy access to the knitting head.







Diameter in inch	Gauge	Number of feeds	Maximum Speed (RPM)
26"	10 - 44	78	46
28"	10 - 44	84	43
30"	10 - 44	90	40
32"	10 - 44	96	38
34"	10 - 44	102	35
36"	10 - 44	108	33
38"	10 - 44	114	32
40"	10 - 44	120	30
42"	10 - 44	126	29

Frame	Fabric roll/MM	Fabric size/MM
Tubular standard	500	
Tubular industrial	780	+ 500
Tubular industrial	1080	+ 800
Open width standard	380	
Open width industrial	600	+ 300

Standard equipment
Aluminum side creel
Positive feeding units
Individual cam shells prepared to receive up to 4 cam tracks
Zirconium yarn guides suitable for three yarn plaiting
Automatic oiling system
Electronic motor drive(inverter)
LFA-Yarn input measuring device
Centralized stitch control
Eletronic needles detector
Motorized slitting and fabric opening system (Open width)

Optionals
Lycra feeding units
Open width frame (26" - 32", 220cm - above 34",245 cm)
Lapping device system(tubular frame)
Industrial frame(both tubular and open width)
Three thread fleece conversion kit (30"- 32"- 34"- 36")

Application area	
Underwear, Sportswear, Swimwear, Medical Textiles	







SANTONI SPA